



highblue®

THE BRIGHTER IDEA

Taking
Innovation
To New Depths

20
24

C o n t e n t

AL250	97			Gloves, Hoods & Handles	118		
AL250 Camouflage	88	Camera Arms	123	Globe Filters	120		
AL450WM Tail	95	Camera Clips & Accessories	123	HL450N	105		
AL450WM Tail Camouflage	87	Camera Trays	111	HL450XW	105	VL4600P	39
AL450NM Tail II	96	Camera Filters	115	HL1000N	104	VL4600PB	17
AL450NM Tail II Camouflage	86	CB4000P	51	HL1000XW	104	VL6200P	37
AL450 Strobe	84	CB4000PBRC	11	HL1000XWN	103	VL9000P Tri Color	35
ALI300RAFO	94	CB7200P	49	Light Filters	119	VLI1000P	33
ALI300NP	91	CB7200PB	15	Light Head	78	VLI1000PBRC	7
ALI300NP Camouflage	85	CB11000P	47	Outdoor Dry Bags	121	VL20000P Pro Mini	31
ALI200NP IR	24	CB11000PBRC	9	Optical Fibre	118	VL20000PBRC	3
ALI300WP	92	CB16500P	45	Protective Case Series	106	VL20000P Pro Mini Tri Color	29
ALI200WP IR	24	CB16500PBRC	5	RGB White II	98	VL36000P	27
ALI300XWP	93	CB30000P II	43	Red Spot Light & Green Spot Light	106	VL36000PBRC	1
ALI300NP Tail	89	CB60000P	41	Snoots	119	VL65000P	25
ALI300WP Tail	90	CF450M	101	Sport Water Bottle	126	VTL2900P	64
ALI300 Strobe	83	CFI300P	100	Spring Cord	120	VTL2900PB	21
ALI800NP II	81	CFI800P	99	TL2900P	77	VTL4200P	63
ALI800WP	82	Chargers	116	TL3800P	76	VTL4200PB	19
AL2000XWP Tri Color	80	Combo Packs	107	TL3800P Supreme	75	VTL9000P	61
AL2900XWP	79	Controller	118	TL3800P Supreme Pro	73	VTL9000PB	13
AL2900WPB	23	Easy Clip Lights	102	TL5200P	71	VTL9000 Max	57
Ambient Filters	117	Easy Release Mount Series	121	TL5200P Backmount / Sidemount	69	VTL9000P Backmount / Sidemount	59
Backpack	125	Float Arms, Flexi Arms	122	TL8000P Mini	67	VTLI1000P	55
Batteries	116	Fluorodive Kits	115	TL9000P	65	VTLI3500P Max	53

VL36000 PBRC



36000 LUMENS

**ANGLE OF LIGHT BEAM
160° WIDE BEAM**

SPECIFICATIONS

Light source	45 x XML LED + 10 x XPE Red LED + 16 x XPE Blue LED
Light output	9000 Lm (level I), 18000 Lm (level II), 36000 Lm (level III)
Light output (Red color mode)	1200 Lm
Light output (Blue color mode)	113 Lm (level I), 225 Lm (level II), 450 Lm (level III)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x8
Angle of light beam	160° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level III), 3 hrs (level II) and 6 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 85 x L. 144.6 mm
Weight in air	1391 g (including battery)
Buoyancy in seawater	-597 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Yellow plate	Included

SPECIFICATIONS for CONTROLLER

Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	CR2032x2
Maximum depth	100 m tested
Size	Dia. 30 x L. 98.3 mm
Weight in air	110 g (including battery)
Buoyancy in seawater	-51 g (including battery)
Switching system	Push button with battery indicator

Li ion Rechargeable Battery Ultra Power LED Video Light with Blue Light with Remote Control Option

- 3 levels of brightness for cool white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Easy to change up the battery pack BATCELL21700x8
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.
- 45pcs XML LED to provide 36000 lumens



- Comes with ball joint for easy system setup
- Place to insert the optical fibre
- Comes with protective case for VL36000PBRC
- Ergonomic aluminum handle comes in a package
- Comes with yellow plate.
- Optical fibre. Sold separately.
- Controller kit set. Sold separately.
- Set-up for the Controller.

VL20000 PBRC



20000 LUMENS

ANGLE OF LIGHT BEAM
160° WIDE BEAM

- 3 levels of brightness for cool white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELL I8650x7 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.
- Ergonomic aluminum handle comes in a package



SPECIFICATIONS

Light source	24 x XML LED + 8 x XPE Red LED + 14 x XPE Blue LED
Light output	5000 Lm (level I), 10000 Lm (level II), 20000 Lm (level III)
Light output (Red color mode)	1000 Lm
Light output (Blue color mode)	113 Lm (level I), 225 Lm (level II), 450 Lm (level III)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x7
Angle of light beam	160° wide beam
Color temperature	6500K
Burn time	2 hrs (level III), 4 hrs (level II) and 8 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 70 x L. 142.5 mm
Weight in air	774 g (including battery)
Buoyancy in seawater	-291 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

SPECIFICATIONS for CONTROLLER

Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	CR2032x2
Maximum depth	100 m tested
Size	Dia. 30 x L. 98.3 mm
Weight in air	110 g (including battery)
Buoyancy in seawater	-51 g (including battery)
Switching system	Push button with battery indicator

Li ion Rechargeable Battery Super Power LED Video Light with Blue Light with Remote Control Option



- 24pcs XML LED to provide 20000 lumens
- Comes with ball joint for easy system setup
- Comes with protective case for VL 20000PBRC
- Comes with yellow plate.
- Optical fibre. Sold separately.
- Controller kit set. Sold separately.
- Set-up for the Controller.

CB16500 PBRC



16500 LUMENS

**ANGLE OF LIGHT BEAM
160° WIDE BEAM**

- 3 levels of brightness for warm white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color /Green color / Red color / Flash Red color
- BATCELL I8650x7 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.
- COB LED to provide 16500 lumens



SPECIFICATIONS

Light source	COB LED + 8 x XPE Red LED + 8 x XPE Blue LED
Light output	4125 Lm (level I), 8250 Lm (level II), 16500 Lm (level III)
Light output (Red color mode)	1000 Lm
Light output (Blue color mode)	55 Lm (level I), 110 Lm (level II), 220 Lm (level III)
Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x7
Angle of light beam	160° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level III), 3 hrs (level II) and 6 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 70 x L. 142.5 mm
Weight in air	787 g (including battery)
Buoyancy in seawater	-304 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

SPECIFICATIONS for CONTROLLER

Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	CR2032x2
Maximum depth	100 m tested
Size	Dia. 30 x L. 98.3 mm
Weight in air	110 g (including battery)
Buoyancy in seawater	-51 g (including battery)
Switching system	Push button with battery indicator

**Li ion Rechargeable Battery Super Power
LED Video Light with High Color Rendering Index
with Blue Light with Remote Control Option**



- Comes with ball joint for easy system setup
- Place to insert the optical fibre.
- Comes with protective case for CB 16500PBRC.
- Ergonomic aluminum handle comes in a package
- Comes with yellow plate.
- Optical fibre. Sold separately.
- Controller kit set. Sold separately.
- Set-up for the Controller.

VL11000 PBRC


11000 lumens

BUILT-IN BLUE LIGHT

BUILT-IN RED LIGHT

Changeable light head

ERM EASY RELEASE MOUNT



SPECIFICATIONS

Light source	15 x XML LED + 6 x XPE Red LED + 8 x XPE Blue LED
Light output	2750 Lm (level I), 5500 Lm (level II), 11000 Lm (level III)
Light output (Red color mode)	500 Lm
Light output (Blue color mode)	55 Lm (level I), 110 Lm (level II), 220 Lm (level III)
Casing material	Aluminum alloy Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x4
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2.5 hrs (level III), 5 hrs (level II) and 10 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 55.4 x L. 130.6 mm
Weight in air	467 g (including battery)
Buoyancy in seawater	-184 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

SPECIFICATIONS for CONTROLLER

Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	CR2032x2
Maximum depth	100 m tested
Size	Dia. 30 x L. 98.3 mm
Weight in air	110 g (including battery)
Buoyancy in seawater	-51 g (including battery)
Switching system	Push button with battery indicator

Li ion Rechargeable Battery High Power LED Video Light with Blue Light with Remote Control Option

- 3 levels of brightness for cool white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELL I8650x4 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.
- Comes with ball joint for easy system setup



- Removable yellow filter enhances warmer color tone
- Sturdy glove for hands-free operation underwater
- Comes with yellow plate.
- Comes with random color outdoor dry bag
- Optical fibre. Sold separately.
- Controller kit set. Sold separately.
- Set-up for the Controller.

CB11000 PBRC

11000 lumens

BUILT-IN BLUE LIGHT

BUILT-IN RED LIGHT

changeable light head

ERM EASY RELEASE MOUNT



SPECIFICATIONS

Light source	COB LED + 6 x XPE Red LED + 8 x XPE Blue LED
Light output	2750 Lm (level I), 5500 Lm (level II), 11000 Lm (level III)
Light output (Red color mode)	500 Lm
Light output (Blue color mode)	55 Lm (level I), 110 Lm (level II), 220 Lm (level III)
Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x4
Angle of light beam	120° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level III), 3 hrs (level II) and 6 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 140.6 mm
Weight in air	679 g (including battery)
Buoyancy in seawater	-283 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

SPECIFICATIONS for CONTROLLER

Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	CR2032x2
Maximum depth	100 m tested
Size	Dia. 30 x L. 98.3 mm
Weight in air	110 g (including battery)
Buoyancy in seawater	-51 g (including battery)
Switching system	Push button with battery indicator

Li ion Rechargeable Battery High Power LED Video Light with High Color Rendering Index with Blue Light with Remote Control Option

- 3 levels of brightness for warm white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELL21700x4 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.
- Comes with ball joint for easy system setup



- Place to insert the optical fibre.
- Snoot connector for CB 11000PBRC. Sold separately.
- Sturdy glove for hands-free operation underwater
- Comes with yellow plate.
- Comes with random color outdoor dry bag
- Optical fibre. Sold separately.
- Controller kit set. Sold separately.
- Set-up for the Controller.

CB4000 PBRC



SPECIFICATIONS

Light source	COB LED + 3 x XPE Red LED + 3 x XPE Blue LED
Light output	1000 Lm (level I), 2000 Lm (level II), 4000 Lm (level III)
Light output (Red color mode)	300 Lm
Light output (Blue color mode)	23 Lm (level I), 45 Lm (level II), 90 Lm (level III)
Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x3
Angle of light beam	120° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level III), 3 hrs (level II) and 6 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 50 x L. 134 mm
Weight in air	410 g (including battery)
Buoyancy in seawater	-177 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

SPECIFICATIONS for CONTROLLER

Casing material	Aluminum alloy, Anti-corrosive anodized
Power source	CR2032x2
Maximum depth	100 m tested
Size	Dia. 30 x L. 98.3 mm
Weight in air	110 g (including battery)
Buoyancy in seawater	-51 g (including battery)
Switching system	Push button with battery indicator

Li ion Rechargeable Battery LED Video Light with High Color Rendering Index with Blue Light with Remote Control Option

- 3 levels of brightness for warm white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELL I8650x3 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.
- Comes with ball joint for easy system setup



- Place to insert the optical fibre.
- Snoot connector for CB4000PBRC. Sold separately.
- Sturdy glove for hands-free operation underwater
- Comes with yellow plate.
- Comes with random color outdoor dry bag
- Optical fibre. Sold separately.
- Controller kit set. Sold separately.
- Set-up for the Controller.

VTL9000 PB

9000 / 1300 lumens / 1300 lumens
WIDE SPOT

BUILT-IN BLUE LIGHT

BUILT-IN RED LIGHT

changeable light head

ERM EASY RELEASE MOUNT

NEW



SPECIFICATIONS

Light source	11 x XML LED + 6 x XPE Red LED + 8 x XPE Blue LED
Light output (Flood beam mode)	2250 Lm (level I), 4500 Lm (level II), 9000 Lm (level III)
Light output (Spot beam mode)	1300 Lm
Light output (Red color mode)	500 Lm
Light output (Blue color mode)	45 Lm (level I), 90 Lm (level II), 180 Lm (level III)
Casing Material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLI8650x4
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	3 hrs (level III), 6 hrs (level II) and 12 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 150.3 mm
Weight in air	550 g (including battery)
Buoyancy in seawater	-205 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

120° WIDE BEAM 10° NARROW BEAM

- 3 Levels of brightness for cool white mode, 3 levels of brightness for blue color mode, 1 level of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.



Li ion Rechargeable Battery High Power LED Video / Tech Light with Blue Light



- Removable yellow filter enhances warmer color tone
- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- BATCELLI8650x4 Li ion Rechargeable Battery
- Comes with yellow plate
- Comes with random color outdoor dry bag

CB7200PB

7200 lumens

BUILT-IN BLUE LIGHT

BUILT-IN RED LIGHT

changeable light head

ERM EASY RELEASE MOUNT



SPECIFICATIONS

Light source	COB LED + 6 x XPE Red LED + 8 x XPE Blue LED
Light output	1800 Lm (level I), 3600 Lm (level II), 7200 Lm (level III)
Light output (Red color mode)	500 Lm
Light output (Blue color mode)	55 Lm (level I), 110 Lm (level II), 220 Lm (level III)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x4
Angle of light beam	120° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	2 hrs (level III), 4 hrs (level II) and 8 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 134.6 mm
Weight in air	653 g (including battery)
Buoyancy in seawater	-272 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

Li ion Rechargeable Battery High Power LED Video Light with High Color Rendering Index with Blue Light

- 3 levels of brightness for warm white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color /Green color / Red color / Flash Red color
- BATCELL21700x4 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.



- Snoot connector for CB 7200PB. Sold separately.
- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- Comes with random color outdoor dry bag
- Comes with yellow plate.

VL4600 PB


4600 lumens

BUILT-IN BLUE LIGHT

BUILT-IN RED LIGHT

changeable light head

ERM EASY RELEASE MOUNT



SPECIFICATIONS

Light source	6 x XML LED + 4 x XPE Red LED + 4 x XPE Blue LED
Light output	1150 Lm (level I), 2300 Lm (level II) 4600 Lm (level III)
Light output (Red color mode)	300 Lm
Light output (Blue color mode)	30 Lm (level I), 60 Lm (level II) 120 Lm (level III)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level III), 3 hrs (level II) and 6 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 44 x L. 121.1 mm
Weight in air	318 g (including battery)
Buoyancy in seawater	-167 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

Li ion Rechargeable Battery LED Video Light with Blue Light

- 3 levels of brightness for cool white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color /Green color / Red color / Flash Red color
- BATCELL32650 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.
- Comes with ball joint for easy system setup



- Sturdy glove for hands-free operation underwater
- Removable yellow filter enhances warmer color tone
- Comes with USB charger
- Comes with random color outdoor dry bag
- Comes with yellow plate.

VTL4200PB

4200 / 1300
lumens / lumens
WIDE SPOT



SPECIFICATIONS

Light source	7 x XML LED + 2 x XBD Red LED + 4 x XBD Blue LED
Light output (Flood beam mode)	1050 Lm (level I), 2100 Lm (level II) 4200 Lm (level III)
Light output (Spot beam mode)	1300 Lm
Light output (Red color mode)	150 Lm
Light output (Blue color mode)	20 Lm (level I), 40 Lm (level II) 80 Lm (level III)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level III), 3 hrs (level II) and 6 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 55.5 x L. 140.6 mm
Weight in air	432 g (including battery)
Buoyancy in seawater	-205 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

120° WIDE BEAM

10° NARROW BEAM

- 3 levels of brightness for cool white mode, 3 levels of brightness for blue color mode, 1 level of brightness for spot beam mode and 1 level of brightness for red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- BATCELL32650 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.



Li ion Rechargeable Battery LED Video / Tech Light with Blue Light



- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- Removable yellow filter enhances warmer color tone
- Comes with USB charger
- Comes with random color outdoor dry bag
- Comes with yellow plate.

VTL2900 PB

2900 / 1000 lumens / 1000 lumens
WIDE SPOT



SPECIFICATIONS

Light source	7 x LED + 2 x XBD Red LED + 2 x XBD Blue LED
Light output (Flood beam mode)	725 Lm (level I), 1450 Lm (level II) 2900 Lm (level III)
Light output (Spot beam mode)	1000 Lm
Light output (Red color mode)	100 Lm
Light output (Blue color mode)	10 Lm (level I), 20 Lm (level II) 40 Lm (level III)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	100° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level III), 3 hrs (level II) and 6 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 44 x L. 128.7 mm
Weight in air	339 g (including battery)
Buoyancy in seawater	-177 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included

100° WIDE BEAM 10° NARROW BEAM

- 3 levels of brightness for cool white mode, 3 levels of brightness for blue color mode, 1 level of brightness for spot beam mode and 1 level of brightness for red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- BATCELL32650 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result.



Li ion Rechargeable Battery LED Video / Tech Light with Blue Light



- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- Removable yellow filter enhances warmer color tone
- Comes with USB charger
- Comes with random color outdoor dry bag
- Comes with yellow plate.

AL2900

Black Molly
VIIB
XWPB

2900 lumens



Li ion Rechargeable Battery LED Light with Blue Light



SPECIFICATIONS

Light source	4 x XML LED + 2 x XPE Red LED + 2 x XPE Blue LED
Light output	725 Lm (level I), 1450 Lm (level II), 2900 Lm (level III)
Light output (Red color mode)	150 Lm
Light output (Blue color mode)	15 Lm (level I), 30 Lm (level II), 60 Lm (level III)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL 26650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level III), 4 hrs (level II) and 8 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 126.8 mm
Weight in air	218 g (including battery)
Buoyancy in seawater	-105 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included
Yellow plate	Included



- 3 levels of brightness for cool white mode, 3 levels of brightness for blue color mode, 1 level of brightness for red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Built-in red color led enhances focusing performance
- Built-in blue color led for fluorodiving performance. Go with yellow plate for better result
- Removable yellow filter enhances warmer color tone
- Comes with yellow plate.
- BATCELL26650 Li ion Rechargeable Battery
- Comes with ball joint for easy system setup
- Protective case for AL 2900XWPB. Sold separately.
- Protective case for AL 2900XWPB and Single Arm Tray. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1200 NPIR



SPECIFICATIONS

Light source	IR (940nm)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	10° narrow beam
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 33.2 x L. 139.8 mm
Weight in air	168 g (including battery)
Buoyancy in seawater	-76 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 levels of brightness, and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELL 18650 Li ion Rechargeable Battery
- 940nm IR

AL1200 WPIR



SPECIFICATIONS

Light source	IR (940nm)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	85° wide beam
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 126.3 mm
Weight in air	162 g (including battery)
Buoyancy in seawater	-84 g (including battery)
Switching system	Push button with battery indicator
Front glass	Concave lens
Lanyard	Included



- 4 levels of brightness, and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELL 18650 Li ion Rechargeable Battery
- Comes with random color outdoor dry bag

VL65000P

65000
lumens



THE MOST BRIGHTNESS
65000 LUMENS

ANGLE OF LIGHT BEAM
160° WIDE BEAM

1. 4 levels of brightness, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design. Press two keys at the same time to come up 100%, 50%, 25%, 10% four power level setting.
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. 2x BATCELL60000 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	72 x XML LED + 20 x XPE Red LED
Light output	6500 Lm (level I), 16250 Lm (level II) 32500 Lm (level III), 65000 Lm (level IV)
Light output (Red color mode)	2000 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 2 x BATCELL60000
Angle of light beam	160° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 120 x L. 240 mm
Weight in air	3766 g (including battery)
Buoyancy in seawater	-1107 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass

Li ion Rechargeable Battery Huge Power LED Video Light



5. Easy to charge up the battery pack BATCELL60000
6. 72pcs XML LED to provide 65000 lumens
7. Comes with ball joint for easy system setup
8. Make use of double clip and single arm to make the handle. Comes in a package.
9. Comes with protective case for VL65000P.

VL36000P

36000
lumens

BUILT-IN
RED
LIGHT

Slim
Size



36000 LUMENS

ANGLE OF LIGHT BEAM
160° WIDE BEAM

1. 4 levels of brightness | level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. Easy to charge up the battery pack BATCELL 21700x8
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	45 x XML LED + 10 x XPE Red LED
Light output	3600 Lm (level I), 9000 Lm (level II) 18000 Lm (level III), 36000 Lm (level IV)
Light output (Red color mode)	1200 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x8
Angle of light beam	160° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 85 x L. 144.6 mm
Weight in air	1391 g (including battery)
Buoyancy in seawater	-597 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass

Li ion Rechargeable Battery Ultra Power LED Video Light



5. 45pcs XML LED to provide 36000 lumens
6. Comes with ball joint for easy system setup
7. Ergonomic aluminum handle comes in a package
8. Comes with protective case for VL36000P.

VL20000P | PRO MINI TRI COLOR

20000 lumens

BUILT-IN YELLOW LIGHT

BUILT-IN RED LIGHT

Upgraded



20000 LUMENS

ANGLE OF LIGHT BEAM
160° WIDE BEAM

1. 3 Levels of brightness for cool white mode, 3 Levels of brightness for warm white mode, 1 level of brightness of Red color mode, and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELLI8650x7 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	32 x XML LED + 8 x XPE Red LED
Light output (Cool white mode)	5000 Lm (level I), 10000 Lm (level II) 20000 Lm (level III)
Light output (Warm white mode)	2250 Lm (level I), 4500 Lm (level II) 9000 Lm (level III)
Light output (Red color mode)	1000 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLI8650x7
Angle of light beam	160° wide beam
Color temperature	6500K cool white and 5500K warm white
Burn time	2 hrs (level III), 4 hrs (level II) and 8 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 70 x L. 136 mm
Weight in air	772 g (including battery)
Buoyancy in seawater	-313 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery Super Power LED Video Light with Three Color Output



5. Built-in yellow color led enhances warmer color tone
6. Ergonomic aluminum handle comes in a package
7. FILFLUORO15000 Fluorodive filter for VL 20000P Pro Mini Tri Color. Sold separately.
8. Comes with ball joint for easy system setup
9. Comes with protective case for VL 20000P Pro Mini Tri Color.

VL20000 P | PRO MINI

20000
lumens

BUILT-IN
RED
LIGHT

Upgraded



20000 LUMENS

ANGLE OF LIGHT BEAM
160° WIDE BEAM

1. 4 levels of brightness, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL I8650x7 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	24 x XML LED + 8 x XPE Red LED
Light output	2000 Lm (level I), 5000 Lm (level II) 10000 Lm (level III), 20000 Lm (level IV)
Light output (Red color mode)	1000 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x7
Angle of light beam	160° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 70 x L. 136 mm
Weight in air	757 g (including battery)
Buoyancy in seawater	-298 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery Super Power LED Video Light



5. 24pcs XML LED to provide 20000 lumens
6. Ergonomic aluminum handle comes in a package
7. FILFLUORO I5000 Fluorodive filter for VL 20000P Pro Mini. Sold separately.
8. Comes with ball joint for easy system setup
9. Comes with protective case for VL 20000P Pro Mini.

VL11000P

11000
lumens

BUILT-IN
RED
LIGHT

changeable
light head

ERM
EASY RELEASE
MOUNT



1. 4 Levels of brightness, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL I8650x4 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	15 x XML LED + 6 x XPE Red LED
Light output	1100 Lm (level I), 2750 Lm (level II) 5500 Lm (level III), 11000 Lm (level IV)
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x4
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2.5 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 25 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 55.4 x L. 130.6 mm
Weight in air	457 g (including battery)
Buoyancy in seawater	-173 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery High Power LED Video Light



5. Removable yellow filter enhances warmer color tone
6. Sturdy glove for hands-free operation underwater
7. Comes with ball joint for easy system setup
8. Comes with random color outdoor dry bag

VL9000 P TRI COLOR

9000 lumens



- 3 Levels of brightness for cool white mode, 3 Levels of brightness for warm white mode, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELLI8650x4 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	15 x XML LED + 6 x XPE Red LED
Light output (Cool white mode)	2250 Lm (level I), 4500 Lm (level II) 9000 Lm (level III)
Light output (Warm white mode)	1125 Lm (level I), 2250 Lm (level II) 4500 Lm (level III)
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLI8650x4
Angle of light beam	120° wide beam
Color temperature	6500K cool white and 5500K warm white
Burn time	3 hrs (level III), 6 hrs (level II) and 12 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 55.4 x L. 130.6 mm
Weight in air	457 g (including battery)
Buoyancy in seawater	-173 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery High Power LED Video Light with Three Color Output



- Built-in yellow color led enhances warmer color tone
- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- Comes with random color outdoor dry bag

VL6200P

6200
lumens

BUILT-IN
RED
LIGHT

changeable
light head

ERM
EASY RELEASE
MOUNT



1. 4 Levels of brightness, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL I8650x3 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	6 x XML LED + 4 x XBD Red LED
Light output	620 Lm (level I), 1550 Lm (level II) 3100 Lm (level III), 6200 Lm (level IV)
Light output (Red color mode)	300 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x3
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 50 x L. 126.6 mm
Weight in air	381 g (including battery)
Buoyancy in seawater	-163 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery LED Video Light



5. Sturdy glove for hands-free operation underwater
6. Comes with ball joint for easy system setup
7. Comes with random color outdoor dry bag

VL4600P

4600
lumens



Available in 3 colors

1. 4 levels of brightness for Flood beam mode, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL 32650 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	6 x XML LED + 4 x XPE Red LED
Light output (Flood beam mode)	460 Lm (level I), 1150 Lm (level II) 2300 Lm (level III), 4600 Lm (level IV)
Light output (Red color mode)	300 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 44 x L. 121.1 mm
Weight in air	318 g (including battery)
Buoyancy in seawater	-167 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery LED Video Light



5. Comes with ball joint for easy system setup
6. Removable yellow filter enhances warmer color tone
7. Sturdy glove for hands-free operation underwater
8. Comes with USB charger
9. Comes with random color outdoor dry bag

CB60000P

60000
lumens

BUILT-IN
RED
LIGHT



60000 LUMENS

ANGLE OF LIGHT BEAM
160° WIDE BEAM

- 4 levels of brightness, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design. Press two keys at the same time to come up 100%, 50%, 25%, 10% four power level setting.
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- 2xBATCELL60000 Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	COB LED + 20 x XPE Red LED
Light output	6000 Lm (level I), 15000 Lm (level II) 30000 Lm (level III), 60000 Lm (level IV)
Light output (Red color mode)	2000 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 2 x BATCELL60000
Angle of light beam	160° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 120 x L. 240 mm
Weight in air	3766 g (including battery)
Buoyancy in seawater	-1107 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass

Li ion Rechargeable Battery Huge Power LED Video
Light with High Color Rendering Index



- Easy to charge up the battery pack BATCELL60000
- COB LED to provide 60000 lumens
- Comes with ball joint for easy system setup
- Make use of double clip and single arm to make the handle. Comes in a package.
- Comes with protective case for CB 60000P.

CB30000 P II

30000
lumens

BUILT-IN
RED
LIGHT

Slim
Size



30000 LUMENS

ANGLE OF LIGHT BEAM
160° WIDE BEAM

1. 4 levels of brightness 1 level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL21700x8 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	COB LED + 10 x XPE Red LED
Light output	3000 Lm (level I), 7500 Lm (level II) 15000 Lm (level III), 30000 Lm (level IV)
Light output (Red color mode)	1200 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x8
Angle of light beam	160° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 85 x L. 144.6 mm
Weight in air	1391 g (including battery)
Buoyancy in seawater	-597 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass

Li ion Rechargeable Battery Ultra Power LED Video
Light with High Color Rendering Index



5. COB LED to provide 30000 lumens
6. Comes with ball joint for easy system setup
7. Ergonomic aluminum handle comes in a package
8. Comes with protective case for CB30000P II.

CB16500P

16500
lumens

BUILT-IN
RED
LIGHT



16500 LUMENS

ANGLE OF LIGHT BEAM
160° WIDE BEAM

1. 4 levels of brightness | level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL I8650x7 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	COB LED + 8 x XPE Red LED
Light output	1650 Lm (level I), 4125 Lm (level II) 8250 Lm (level III), 16500 Lm (level IV)
Light output (Red color mode)	1000 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x7
Angle of light beam	160° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 70 x L. 136 mm
Weight in air	776 g (including battery)
Buoyancy in seawater	-317 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery Super Power LED
Video Light with High Color Rendering Index



5. COB LED to provide 16500 lumens
6. Comes with ball joint for easy system setup
7. Ergonomic aluminum handle comes in a package
8. Comes with protective case for CB16500P.
9. FILFLUORO I5000 Fluorodive filter for CB16500P. Sold separately.

CB11000 P

11000
lumens

BUILT-IN
RED
LIGHT

changeable
light head

ERM
EASY RELEASE
MOUNT



1. 4 levels of brightness | level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL21700x4 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	COB LED + 6 x XPE Red LED
Light output	1100 Lm (level I), 2750 Lm (level II) 5500 Lm (level III), 11000 Lm (level IV)
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x4
Angle of light beam	120° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 134.6 mm
Weight in air	654 g (including battery)
Buoyancy in seawater	-273 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery High Power LED Video Light with High Color Rendering Index



5. Snoot connector for CB 11000P. Sold separately.
6. Sturdy glove for hands-free operation underwater
7. Comes with ball joint for easy system setup
8. Comes with random color outdoor dry bag

CB7200 P

7200
lumens

BUILT-IN
RED
LIGHT

changeable
light head

ERM
EASY RELEASE
MOUNT



1. 4 levels of brightness | level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL21700x4 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	COB LED + 6 x XPE Red LED
Light output	720 Lm (level I), 1800 Lm (level II) 3600 Lm (level III), 7200 Lm (level IV)
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x4
Angle of light beam	120° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 134.6 mm
Weight in air	653 g (including battery)
Buoyancy in seawater	-272 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery High Power LED Video Light with High Color Rendering Index



5. Snoot connector for CB 7200P. Sold separately.
6. Sturdy glove for hands-free operation underwater
7. Comes with ball joint for easy system setup
8. Comes with random color outdoor dry bag

CB4000P

4000
lumens

BUILT-IN
RED
LIGHT

changeable
light head

ERM
EASY RELEASE
MOUNT



1. 4 levels of brightness | level of brightness of Red color mode and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL18650x3 Li ion Rechargeable Battery
4. Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	COB LED + 4 x XPE Red LED
Light output	400 Lm (level I), 1000 Lm (level II) 2000 Lm (level III), 4000 Lm (level IV)
Light output (Red color mode)	300 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x3
Angle of light beam	120° wide beam
Color temperature	5000K
Color Rendering Index	Ra 85
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 50 x L. 130.3 mm
Weight in air	393 g (including battery)
Buoyancy in seawater	-168 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery LED Video Light with High Color Rendering Index



5. Snoot connector for CB 4000P. Sold separately.
6. Sturdy glove for hands-free operation underwater
7. Comes with ball joint for easy system setup
8. Comes with random color outdoor dry bag

VTL13500 P MAX

13500 / 2900
lumens / lumens
WIDE SPOT



SPECIFICATIONS

Light source	18 x LED
Light output (Flood beam mode)	3375 Lm (level I) 6750 Lm (level II), 13500 Lm (level III)
Light output (Spot beam mode)	725 Lm (level I) 1450 Lm (level II), 2900 Lm (level III)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x4
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	2.5 hrs (level III), 5 hrs (level II) and 10 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 154.3 mm
Weight in air	686 g (including battery)
Buoyancy in seawater	-245 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

120° WIDE BEAM 10° NARROW BEAM

- 3 Levels of brightness for Flood beam mode, and 3 levels of brightness for Spot beam mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- Removable red filter enhances focusing performance



Li ion Rechargeable Battery Super Power LED Video / Tech Light



- Removable yellow filter enhances warmer color tone
- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- BATCELL21700x4 Li ion Rechargeable Battery
- Comes with random color outdoor dry bag

VTL11000 P

11000 / 1300
lumens / lumens
WIDE SPOT



highblue
VTL11000P

SPECIFICATIONS

Light source	16 x XML LED
Light output (Flood beam mode)	1100 Lm (level I), 2750 Lm (level II) 5500 Lm (level III), 11000 Lm (level IV)
Light output (Spot beam mode)	1300 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLI8650x4
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	2.5 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 25 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 150.3 mm
Weight in air	548 g (including battery)
Buoyancy in seawater	-203 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

120° WIDE BEAM 10° NARROW BEAM

- 4 Levels of brightness for Flood beam mode and 1 level of brightness for Spot beam mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- Removable red filter enhances focusing performance



Li ion Rechargeable Battery High Power LED Video / Tech Light



- Removable yellow filter enhances warmer color tone
- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- BATCELLI8650x4 Li ion Rechargeable Battery
- Comes with random color outdoor dry bag

VTL9000 P MAX

9000 / 2900 lumens
WIDE / SPOT



SPECIFICATIONS

Light source	13 x LED + 6 x XPE Red LED
Light output (Flood beam mode)	2250 Lm (level I) 4500 Lm (level II), 9000 Lm (level III)
Light output (Spot beam mode)	725 Lm (level I) 1450 Lm (level II), 2900 Lm (level III)
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I8650x4
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	3 hrs (level III), 6 hrs (level II) and 12 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 150.3 mm
Weight in air	548 g (including battery)
Buoyancy in seawater	-203 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

120° WIDE BEAM 10° NARROW BEAM

- 3 Levels of brightness for Flood beam mode, 3 levels of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- Built-in red color led enhances focusing performance



Li ion Rechargeable Battery High Power LED Video / Tech Light



- Removable yellow filter enhances warmer color tone
- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- BATCELL I8650x4 Li ion Rechargeable Battery
- Comes with random color outdoor dry bag

VTL9000^P Backmount

9000 / 1300 lumens
WIDE / SPOT



Li ion Rechargeable Battery High Power LED Video/Tech Light with Battery Canister

120° WIDE BEAM
10° NARROW BEAM

SPECIFICATIONS

Light source	11 x XML LED + 6 x XPE Red LED
Light output (Flood beam mode)	900 Lm (level I), 2250 Lm (level II) 4500 Lm (level III), 9000 Lm (level IV)
Light output (Spot beam mode)	1300 Lm
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLCANISTER
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	6 hrs (level IV), 12 hrs (level III) 24 hrs (level II) and 60 hrs (level I)
Maximum depth	100 m tested
Size (Light head)	Dia. 63 x L. 106.5 mm
Size (Canister)	Dia. 60 x L. 202 mm
Weight in air (Light head)	317 g
Weight in air (Canister)	975 g
Buoyancy in seawater (Light head)	-101 g
Buoyancy in seawater (Canister)	-384 g
Switching system	Push button with battery indicator
Cable Length	1.2 meters
Front glass	Tempered optical glass



- 4 Levels of brightness for Flood beam mode, 1 levels of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- BATCELLCANISTER Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Removable yellow filter enhances warmer color tone
- Easy to charge up the battery BATCELLCANISTER
- Comes with ball joint for easy system setup
- Slim fit Goodman handle with connector. Comes in a package
- Comes with protective case for VTL 9000P Backmount.

VTL9000^P Sidemount

9000 / 1300 lumens
WIDE / SPOT



120° WIDE BEAM
10° NARROW BEAM

Li ion Rechargeable Battery High Power LED Video/Tech Light with Battery Canister

SPECIFICATIONS

Light source	11 x XML LED + 6 x XPE Red LED
Light output (Flood beam mode)	900 Lm (level I), 2250 Lm (level II) 4500 Lm (level III), 9000 Lm (level IV)
Light output (Spot beam mode)	1300 Lm
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLCANISTER
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	6 hrs (level IV), 12 hrs (level III) 24 hrs (level II) and 60 hrs (level I)
Maximum depth	100 m tested
Size (Light head)	Dia. 63 x L. 106.5 mm
Size (Canister)	Dia. 60 x L. 212 mm
Weight in air (Light head)	317 g
Weight in air (Canister)	1033 g
Buoyancy in seawater (Light head)	-101 g
Buoyancy in seawater (Canister)	-407 g
Switching system	Push button with battery indicator
Cable Length	1.35 meters
Front glass	Tempered optical glass



- 4 Levels of brightness for Flood beam mode, 1 levels of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- BATCELLCANISTER Li ion Rechargeable Battery
- Built-in red color led enhances focusing performance
- Removable yellow filter enhances warmer color tone
- Easy to charge up the battery BATCELLCANISTER
- Comes with ball joint for easy system setup
- Slim fit Goodman handle with connector. Comes in a package
- Comes with protective case for VTL 9000P Sidemount.

VTL9000P

9000 lumens / 1300 lumens
WIDE SPOT



120° WIDE BEAM 10° NARROW BEAM

- 4 Levels of brightness for Flood beam mode, 1 level of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- Built-in red color led enhances focusing performance



SPECIFICATIONS

Light source	11 x XML LED + 6 x XPE Red LED
Light output (Flood beam mode)	900 Lm (level I), 2250 Lm (level II) 4500 Lm (level III), 9000 Lm (level IV)
Light output (Spot beam mode)	1300 Lm
Light output (Red color mode)	500 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL18650x4
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	3 hrs (level IV), 6 hrs (level III) 12 hrs (level II) and 30 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 63 x L. 150.3 mm
Weight in air	548 g (including battery)
Buoyancy in seawater	-203 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery High Power LED Video / Tech Light



- Removable yellow filter enhances warmer color tone
- Sturdy glove for hands-free operation underwater
- Comes with ball joint for easy system setup
- BATCELL18650x4 Li ion Rechargeable Battery
- Comes with random color outdoor dry bag

VTL4200P

4200 / 1300
lumens / lumens
WIDE SPOT



Li ion Rechargeable Battery
LED Video / Tech Light

120° WIDE BEAM
10° NARROW BEAM



SPECIFICATIONS

Light source	7 x XML LED + 2 x XPE Red LED
Light output (Flood beam mode)	420 Lm (level I), 1050 Lm (level II) 2100 Lm (level III), 4200 Lm (level IV)
Light output (Spot beam mode)	1300 Lm
Light output (Red color mode)	150 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	120° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 55.5 x L. 140.6 mm
Weight in air	432 g (including battery)
Buoyancy in seawater	-205 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness for Flood beam mode, 1 level of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- Sturdy glove for hands-free operation underwater
- Built-in red color led enhances focusing performance.
- Removable yellow filter enhances warmer color tone
- Comes with ball joint for easy system setup
- BATCELL 32650 Li ion Rechargeable Battery
- Comes with USB charger
- Comes with random color outdoor dry bag

VTL2900P

2900 / 1000
lumens / lumens
WIDE SPOT



Li ion Rechargeable Battery
LED Video / Tech Light

100° WIDE BEAM
10° NARROW BEAM



Available in 3 colors

SPECIFICATIONS

Light source	7 x LED + 2 x XPE Red LED
Light output (Flood beam mode)	290 Lm (level I), 725 Lm (level II) 1450 Lm (level III), 2900 Lm (level IV)
Light output (Spot beam mode)	1000 Lm
Light output (Red color mode)	100 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	100° wide beam and 10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 44 x L. 128.7 mm
Weight in air	339 g (including battery)
Buoyancy in seawater	-177 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness for Flood beam mode, 1 level of brightness for Spot beam mode and 1 level of brightness for Red color mode controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Angle of light beam
- Sturdy glove for hands-free operation underwater
- Built-in red color led enhances focusing performance.
- Removable yellow filter enhances warmer color tone
- Comes with ball joint for easy system setup
- BATCELL 32650 Li ion Rechargeable Battery
- Comes with USB charger.
- Comes with random color outdoor dry bag

TL9000P

9000
lumens

Upgraded



1. 4 levels of brightness and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELLI8650x7 Li ion Rechargeable Battery



SPECIFICATIONS

Light source	8 x LED
Light output	900 Lm (level I), 2250 Lm (level II) 4500 Lm (level III), 9000 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLI8650x7
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 78 x L. 143.8 mm
Weight in air	830 g (including battery)
Buoyancy in sea-water	-313 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery Super Power LED Tech Light



4. Ergonomic aluminum handle comes in a package
5. Slim fit Goodman handle with connector. Comes in a package
6. Comes with random color outdoor dry bag



TL8000P Mini



1. 4 levels of brightness and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL21700x4 Li ion Rechargeable Battery
4. Ergonomic aluminum handle comes in a package



SPECIFICATIONS

Light source	8 x LED
Light output	800 Lm (level I), 2000 Lm (level II) 4000 Lm (level III), 8000 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x4
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 78 x L. 144 mm
Weight in air	746 g (including battery)
Buoyancy in sea-water	-302 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery Super Power LED Tech Light



5. Goodman handle with connector or Slim fit Goodman handle with connector. Sold Separately
6. Sturdy Goodman Glove for handy Tech-drive Operation
7. Comes with random color outdoor dry bag

TL5200^P Backmount

5200 lumens **ERM**
EASY RELEASE MOUNT

Li ion Rechargeable Battery
High Power LED Tech Light
with Battery Canister



SPECIFICATIONS

Light source	4 x XML LED
Light output	520 Lm (level I), 1300 Lm (level II) 2600 Lm (level III), 5200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLCANISTER
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	7 hrs (level IV), 14 hrs (level III) 28 hrs (level II) and 70 hrs (level I)
Maximum depth	100 m tested
Size (Light head)	Dia. 72 x L. 88.3 mm
Size (Canister)	Dia. 60 x L. 202 mm
Weight in air (Light head)	380 g
Weight in air (Canister)	975 g
Buoyancy in seawater (Light head)	-134 g
Buoyancy in seawater (Canister)	-384 g
Switching system	Push button with battery indicator
Cable Length	1.2 meters
Front glass	Tempered optical glass



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELLCANISTER Li ion Rechargeable Battery
- Slim fit Goodman handle with connector. Comes in a package
- Easy to charge up the battery BATCELLCANISTER
- Comes with protective case for TL 5200P Backmount.

TL5200^P Sidemount

5200 lumens **ERM**
EASY RELEASE MOUNT

Li ion Rechargeable Battery
High Power LED Tech Light
with Battery Canister



SPECIFICATIONS

Light source	4 x XML LED
Light output	520 Lm (level I), 1300 Lm (level II) 2600 Lm (level III), 5200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLCANISTER
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	7 hrs (level IV), 14 hrs (level III) 28 hrs (level II) and 70 hrs (level I)
Maximum depth	100 m tested
Size (Light head)	Dia. 72 x L. 88.3 mm
Size (Canister)	Dia. 60 x L. 212 mm
Weight in air (Light head)	380 g
Weight in air (Canister)	1033 g
Buoyancy in seawater (Light head)	-134 g
Buoyancy in seawater (Canister)	-407 g
Switching system	Push button with battery indicator
Cable Length	1.35 meters
Front glass	Tempered optical glass



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELLCANISTER Li ion Rechargeable Battery
- Slim fit Goodman handle with connector. Comes in a package
- Easy to charge up the battery BATCELLCANISTER
- Comes with protective case for TL 5200P Sidemount.

TL5200P

5200
lumens



ERM
EASY RELEASE
MOUNT



1. 4 levels of brightness and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELLI8650x4 Li ion Rechargeable Battery
4. Sturdy Goodman Glove for handy Tech-dive operation



SPECIFICATIONS

Light source	4 x XML LED
Light output	520 Lm (level I), 1300 Lm (level II) 2600 Lm (level III), 5200 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELLI8650x4
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 72 x L. 150.3 mm
Weight in air	596 g (including battery)
Buoyancy in sea-water	-222 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery High Power LED Tech Light



5. Ergonomic aluminum handle comes in a package
6. Goodman handle with connector or Slim fit Goodman handle with connector. Sold separately.
7. Comes with random color outdoor dry bag

TL3800^P Supreme Pro

3800
lumens

ERM
EASY RELEASE
MOUNT

LONG
LASTING

NEW



1. 4 Levels of brightness and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color /Green color /Red color /Flash Red color
3. Ergonomic aluminum handle comes in a package
4. BATCELL21700x4 SUPREME Li ion Rechargeable Battery



SPECIFICATIONS

Light source	3 x XML LED
Light output	380 Lm (level I), 950 Lm (level II) 1900 Lm (level III), 3800 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive hard anodized
Power source	Li ion Rechargeable battery pack BATCELL21700x4SUPREME
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	5 hrs (level IV), 10 hrs (level III) 20 hrs (level II) and 50 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 63 x L. 131.7 mm
Weight in air	640 g (including battery)
Buoyancy in sea-water	-269 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

Li ion Rechargeable Battery LED Tech Light



5. Sturdy Goodman Glove for handy Tech-dive operation
6. Goodman handle with connector or Slim fit Goodman handle with connector. Sold separately.
7. Comes with random color outdoor dry bag



TL3800P^P Supreme

3800 lumens

ERM
EASY RELEASE MOUNT

Li ion Rechargeable Battery LED Tech Light



SPECIFICATIONS

Light source	3 x XML LED
Light output	380 Lm (level I), 950 Lm (level II) 1900 Lm (level III), 3800 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack BATCELL I 8650x4SUPREME
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	3 hrs (level IV), 6 hrs (level III) 12 hrs (level II) and 30 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 63 x L. 125 mm
Weight in air	517 g (including battery)
Buoyancy in seawater	-221 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



1. 4 Levels of brightness and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color /Green color /Red color /Flash Red color
3. Ergonomic aluminum handle comes in a package
4. BATCELL I 8650x4 SUPREME Li ion Rechargeable Battery
5. Sturdy Goodman Glove for handy Tech-dive operation
6. Goodman handle with connector or Slim fit Goodman handle with connector. Sold separately.
7. Comes with random color outdoor dry bag

TL3800P

3800 lumens

Changeable Light head

ERM
EASY RELEASE MOUNT

Li ion Rechargeable Battery LED Tech Light



SPECIFICATIONS

Light source	3 x XML LED
Light output	380 Lm (level I), 950 Lm (level II) 1900 Lm (level III), 3800 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 63 x L. 135.6 mm
Weight in air	447 g (including battery)
Buoyancy in seawater	-217 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



1. 4 Levels of brightness and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color /Green color /Red color /Flash Red color
3. Ergonomic aluminum handle comes in a package
4. BATCELL 32650 Li ion Rechargeable Battery
5. Sturdy Goodman Glove for handy Tech-dive operation
6. Goodman handle with connector or Slim fit Goodman handle with connector. Sold separately.
7. Comes with USB charger
8. Comes with random color outdoor dry bag

TL2900P

2900 lumens



Available in 3 colors

Li ion Rechargeable Battery LED Tech Light

SPECIFICATIONS

Light source	3 x LED
Light output	290 Lm (level I), 725 Lm (level II) 1450 Lm (level III), 2900 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 32650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 50 x L. 130 mm
Weight in air	359 g (including battery)
Buoyancy in seawater	-188 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color /Green color /Red color /Flash Red color
- Sturdy Goodman Glove for handy Tech-diver operation
- BATCELL 32650 Li ion Rechargeable Battery
- Ergonomic aluminum handle comes in a package
- Goodman handle with connector or Slim fit Goodman handle with connector. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

LIGHT HEAD



AL2900 Black Molly VII XWP



Li ion Rechargeable Battery LED Light



Available in 2 colors



SPECIFICATIONS

Light source	4 x XML LED + 2 x XPE Red LED
Light output	290 Lm (level I), 725 Lm (level II) 1450 Lm (level III), 2900 Lm (level IV)
Light output (Red color mode)	150 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 26650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 126.8 mm
Weight in air	218 g (including battery)
Buoyancy in seawater	-105 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness, 1 level of brightness of Red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Built-in red color led enhances focusing performance
- Removable yellow filter enhances warmer color tone
- BATCELL26650 Li ion Rechargeable Battery
- Comes with ball joint for easy system setup
- Protective case for AL 2900XWP and Single Arm Tray. Sold separately.
- Protective case for AL 2900XWP. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL2000 Black Molly VI XWP Tri Color



Li ion Rechargeable Battery LED Light with Three Color Output



Available in 2 colors



SPECIFICATIONS

Light source	4 x XML LED + 2 x XPE Red LED
Light output (Cool white mode)	500 Lm (level I), 1000 Lm (level II) 2000 Lm (level III)
Light output (Warm white mode)	500 Lm (level I), 1000 Lm (level II) 2000 Lm (level III)
Light output (Red color mode)	150 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 26650
Angle of light beam	120° wide beam
Color temperature	6500K cool white and 5500K warm white
Burn time	2 hrs (level III), 4 hrs (level II) and 8 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 126.8 mm
Weight in air	218 g (including battery)
Buoyancy in seawater	-105 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 3 Levels of brightness for cool white mode, 3 Levels of brightness for warm white mode 1 level of brightness of Red color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Built-in red color led enhances focusing performance
- Built in yellow color led enhances warmer color tone
- BATCELL26650 Li ion Rechargeable Battery
- Comes with ball joint for easy system setup
- Protective case for AL 2000XWP Tri Color and Single Arm Tray. Sold separately.
- Protective case for AL 2000XWP Tri Color. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1800 NP II

1800 lumens



Li ion Rechargeable Battery
Narrow Beam LED Light



Available in 2 colors

SPECIFICATIONS

Light source	XML LED
Light output	180 Lm (level I), 450 Lm (level II), 900 Lm (level III), 1800 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 26650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III), 6 hrs (level II) and 15 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 35.5 x L. 139.8 mm
Weight in air	235 g (including battery)
Buoyancy in seawater	-113 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELL26650 Li ion Rechargeable Battery
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1800 WP

1800 lumens



Li ion Rechargeable Battery
Wide Beam LED Light



Available in 2 colors

SPECIFICATIONS

Light source	XML LED
Light output	180 Lm (level I), 450 Lm (level II), 900 Lm (level III), 1800 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 26650
Angle of light beam	85° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III), 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 129 mm
Weight in air	228 g (including battery)
Buoyancy in seawater	-120 g (including battery)
Switching system	Push button with battery indicator
Front glass	Concave lens
Lanyard	Included



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- BATCELL26650 Li ion Rechargeable Battery
- Comes with ball joint for easy system setup
- Removable red and yellow filters enhances focusing performances and warm color tone
- Snoot Connector for AL1800WP. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1300 Strobe

1300 lumens



Li ion Rechargeable Battery
LED Strobe Light



SPECIFICATIONS

Light source	XML LED
Light output	1300 Lm
Blinking frequency	60 pulses per minute
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	270°
Burn time	12 hrs
Maximum depth	150 m tested
Size	Dia. 35.5 x L. 152.6 mm
Weight in air	170 g (including battery)
Buoyancy in seawater	-81 g (including battery)
Switching system	Push button with battery indicator
Lanyard	Included



1. On / Off controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. BATCELL 18650 Li ion Rechargeable Battery
4. Comes with random color outdoor dry bag
5. Blinking frequency : 60 pulses per minute
6. Comes with USB charger

AL450 Strobe


450 lumens

LED Aluminium Strobe Light



SPECIFICATIONS

Light source	Cree LED
Light output	450 Lm
Blinking frequency	60 pulses per minute
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	3 x AAA alkaline or Ni-MH batteries
Angle of light beam	270°
Burn time	36 hrs
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 136.7 mm
Weight in air	131 g (including battery)
Buoyancy in seawater	-47 g (including battery)
Switching system	Push button
Lanyard	Included



1. Push on / off button on the bottom
2. 3xAAA stand-alone battery holder
3. Blinking frequency : 60 pulses per minute

AL1300 NP Camouflage

1300 lumens

Slim Size

NEW

Li ion Rechargeable Battery
Narrow Beam LED Light



Available in 5 colors

SPECIFICATIONS

Light source	XML LED
Light output	130 Lm (level I), 325 Lm (level II) 650 Lm (level III), 1300 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 33.2 x L. 139.8 mm
Weight in air	168 g (including battery)
Buoyancy in seawater	-76 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- FILREDNP Red filter for AL1300NP. Sold separately.
- BATCELL 18650 Li ion Rechargeable Battery
- Our light can fit in glove or pouch. Sold separately.
- Comes with USB charger
- Comes with specific camouflage color outdoor dry bag

AL450 NM Tail II Spotter Camouflage

450 lumens

Narrow Beam Aluminum LED Light
with Tail Switch Button



Available in 2 colors

SPECIFICATIONS

- 450 Lumens Cree LED
- Size : Dia.33 x L.121.7 mm
- Aluminum Alloy, anti-corrosive anodized
- 3xAAA alkaline or Ni-MH batteries
- Angle of light beam: 8°
- Up to 4hrs of burn time
- Maximum depth : 100 m tested
- Lanyard included
- 150 g (including batteries) weight in air
- -70 g (including batteries) buoyancy in seawater
- Switching System : Push Button



1. Push on / off button on the bottom
2. 3xAAA stand-alone battery holder
3. AL 450NM Tail II LED with Glove
4. AL 450NM Tail II LED with Pouch
5. AL 450NM Tail II LED with Pouch and Glove

AL450 Camouflage WM Tail

450 lumens

LED Aluminum Diving Light with Tail Switch Button



Available in 2 colors

SPECIFICATIONS

- 450 Lumens Cree LED
- Size : Dia.36 x L.122.6 mm
- Aluminum Alloy, anti-corrosive anodized
- 3xAAA alkaline or Ni-MH batteries
- Angle of light beam: 40°
- Up to 4hrs of burn time
- Maximum depth : 100 m tested
- Lanyard included
- 160 g (including batteries) weight in air
- -74 g (including batteries) buoyancy in seawater
- Switching System : Push Button



1. Push on / off button on the bottom
2. 3xAAA stand-alone battery holder
3. AL 450WM Tail LED with Glove
4. AL 450WM Tail LED with Pouch
5. AL 450WM Tail LED with Pouch and Glove

AL250 Camouflage

250 lumens

Multi-Function Aluminum LED Light



Available in 2 colors

SPECIFICATIONS

Light source	1 x XPG LED
Light output	250 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	2xAA alkaline or Ni-MH batteries
Angle of light beam	8° narrow beam
Color temperature	6500K
Burn time	Up to 2 hrs
Maximum depth	100 m tested
Size	Dia. 28 x L. 147.8 mm
Weight in air	135 g (including battery)
Buoyancy in seawater	-85 g (including battery)
Front glass	Tempered optical glass
Lanyard	Included



1. Light is suitable for multi-function
2. Operate with 2xAA batteries
3. Our light can fit in glove or pouch. Sold separately.

AL1300 NP Tail

1300 lumens



Li ion Rechargeable Battery Narrow Beam LED Light with Tail Switch Button



SPECIFICATIONS

Light source	XML LED
Light output	130 Lm (level I), 325 Lm (level II) 650 Lm (level III), 1300 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 33.2 x L. 152.2 mm
Weight in air	189 g (including battery)
Buoyancy in seawater	-87 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- FILREDNP Red filter for AL1300NP Tail. Sold separately.
- BATCELL 18650 Li ion Rechargeable Battery
- Our light can fit in glove or pouch. Sold separately.
- Protective case for AL 1300NP Tail. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1300 WP Tail

1300 lumens



Li ion Rechargeable Battery Wide Beam LED Light with Tail Switch Button



SPECIFICATIONS

Light source	XML LED
Light output	130 Lm (level I), 325 Lm (level II) 650 Lm (level III), 1300 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	85° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 137.7 mm
Weight in air	177 g (including battery)
Buoyancy in seawater	-88 g (including battery)
Switching system	Push button with battery indicator
Front glass	Concave lens
Lanyard	Included



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Comes with the clip for easy system setup
- Snoot Connector for AL1300WP Tail. Sold separately.
- BATCELL 18650 Li ion Rechargeable Battery
- Removable red and yellow filters enhances focusing performances and warm color tone
- Our light can fit in glove or pouch. Sold separately.
- Protective case for AL 1300WP Tail. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1300 NP

1300 lumens



Li ion Rechargeable Battery Narrow Beam LED Light



SPECIFICATIONS

Light source	XML LED
Light output	130 Lm (level I), 325 Lm (level II) 650 Lm (level III), 1300 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	10° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	150 m tested
Size	Dia. 33.2 x L. 139.8 mm
Weight in air	168 g (including battery)
Buoyancy in seawater	-76 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- FILREDNP Red filter for AL1300NP. Sold separately.
- BATCELL 18650 Li ion Rechargeable Battery
- Our light can fit in glove or pouch. Sold separately.
- Protective case for AL 1300NP. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1300 WP

1300 lumens



Li ion Rechargeable Battery Wide Beam LED Light



SPECIFICATIONS

Light source	XML LED
Light output	130 Lm (level I), 325 Lm (level II) 650 Lm (level III), 1300 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	85° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 126.3 mm
Weight in air	162 g (including battery)
Buoyancy in seawater	-84 g (including battery)
Switching system	Push button with battery indicator
Front glass	Concave lens
Lanyard	Included

- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Comes with the clip for easy system setup
- Snoot Connector for AL1300WP. Sold separately.
- BATCELL 18650 Li ion Rechargeable Battery
- Removable red and yellow filters enhances focusing performances and warm color tone
- Our light can fit in glove or pouch. Sold separately.
- Protective case for AL 1300WP. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1300 XWP

1300 lumens



Slim Size

Li ion Rechargeable Battery
Extra Wide Beam LED Light



SPECIFICATIONS

Light source	XML LED
Light output	130 Lm (level I), 325 Lm (level II) 650 Lm (level III), 1300 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 122.1 mm
Weight in air	160 g (including battery)
Buoyancy in seawater	-84 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Comes with the clip for easy system setup
- Snoot Connector for ALI 300XWP. Sold separately.
- BATCELL 18650 Li ion Rechargeable Battery
- Removable red and yellow filters enhances focusing performances and warm color tone
- Our light can fit in glove or pouch. Sold separately.
- Protective case for AL 1300XWP. Sold separately.
- Comes with USB charger
- Comes with random color outdoor dry bag

AL1300 RAFO

1300 lumens



Slim Size

Upgraded

Li ion Rechargeable Battery Wide Beam
LED Light with Auto-Flash Off Function



SPECIFICATIONS

Light source	XML LED + 2 x XPE Red LED
Light output	130 Lm (level I), 325 Lm (level II) 650 Lm (level III), 1300 Lm (level IV) 150 Lm
Light output (Red collar mode)	150 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	55° wide beam
Color temperature	6500K
AFO interval	0.2sec. +/- 0.1 sec.
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 42.4 x L. 128.3 mm
Weight in air	242 g (including battery)
Buoyancy in seawater	-129 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included

- 4 Levels of brightness, 1 level of brightness of Red Color mode and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Comes with ball joint for easy system setup
- Automatic Flash Off Function AFO interval: 0.2 sec. +/- 0.1 sec.
- Built-in red color led enhances focusing performance
- BATCELL 18650 Li ion Rechargeable Battery
- Comes with USB charger
- Comes with random color outdoor dry bag

AL450 WM TAIL

LED Aluminum Diving Light
with Tail Switch Button



SPECIFICATIONS

- 450 Lumens Cree LED
- Size : Dia.36 x L.122.6 mm
- Aluminum Alloy, anti-corrosive anodized
- 3xAAA alkaline or Ni-MH batteries
- Angle of light beam: 40°
- Up to 4hrs of burn time
- Maximum depth : 100 m tested
- Lanyard included
- 160 g (including batteries) weight in air
- -74 g (including batteries) buoyancy in seawater
- Switching System : Push Button



1. Push on / off button on the bottom
2. 3xAAA stand-alone battery holder
3. AL 450WM Tail LED with Glove
4. AL 450WM Tail LED with Pouch
5. AL 450WM Tail LED with Pouch and Glove

AL450 NM Tail II Spotter

Narrow Beam Aluminum LED Light
with Tail Switch Button



SPECIFICATIONS

- 450 Lumens Cree LED
- Size : Dia.33 x L.121.7 mm
- Aluminum Alloy, anti-corrosive anodized
- 3xAAA alkaline or Ni-MH batteries
- Angle of light beam: 8°
- Up to 4hrs of burn time
- Maximum depth : 100 m tested
- Lanyard included
- 150 g (including batteries) weight in air
- -70 g (including batteries) buoyancy in seawater
- Switching System : Push Button



1. Push on / off button on the bottom
2. 3xAAA stand-alone battery holder
3. AL 450NM Tail II LED with Glove
4. AL 450NM Tail II LED with Pouch
5. AL 450NM Tail II LED with Pouch and Glove

AL250


250 lumens

Multi-Function Aluminum LED Light



SPECIFICATIONS

Light source	1 x XPG LED
Light output	250 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	2xAA alkaline or Ni-MH batteries
Angle of light beam	8° narrow beam
Color temperature	6500K
Burn time	Up to 2 hrs
Maximum depth	100 m tested
Size	Dia. 28 x L. 147.8 mm
Weight in air	135 g (including battery)
Buoyancy in seawater	-85 g (including battery)
Front glass	Tempered optical glass
Lanyard	Included



1. Light is suitable for multi-function
2. Operate with 2xAA batteries
3. Our light can fit in glove or pouch. Sold separately.
4. Available in 5 colors

RGB White II



Li ion Rechargeable Battery 4 Colors LED Light



SPECIFICATIONS

Light source	LED
Light output	500 Lm (white), 120 Lm (red) 40 Lm (blue), 300 Lm (green)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	85° wide beam
Color temperature	6500K
Burn time	2 hrs
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 126.3 mm
Weight in air	162 g (including battery)
Buoyancy in seawater	-84 g (including battery)
Switching system	Push button with battery indicator
Front glass	Concave lens
Lanyard	Included



1. 4 colors of light and SOS controlled by a reliable push button design
2. Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
3. Comes with the clip for easy system setup
4. BATCELL 18650 Li ion Rechargeable Battery
5. Built-in red color LED
6. Built-in green color LED
7. Built-in blue color LED
8. Snoot Connector for RGB White II. Sold separately.
9. Our light can fit in glove or pouch. Sold separately.
10. Comes with USB charger
11. Comes with random color outdoor dry bag

CF1800 P

1800
lumens5X
FocusableLi ion Rechargeable Battery
Changeable Focus LED Light

SPECIFICATIONS

Light source	XML LED
Light output	180 Lm (level I), 450 Lm (level II) 900 Lm (level III), 1800 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 26650
Angle of light beam	7° narrow beam to 37° wide beam
Color temperature	6500K
Burn time	1.5 hrs (level IV), 3 hrs (level III) 6 hrs (level II) and 15 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 169.3 mm
Weight in air	301 g (including battery)
Buoyancy in seawater	-146 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Twist the front to change the focus (Turning force increases with depth)
- BATCELL 26650 Li ion Rechargeable Battery
- Comes with USB charger
- Comes with random color outdoor dry bag

CF1300 P

1300
lumens5X
FocusableSlim
SizeLi ion Rechargeable Battery
Changeable Focus LED Light

SPECIFICATIONS

Light source	XML LED
Light output	130 Lm (level I), 325 Lm (level II) 650 Lm (level III), 1300 Lm (level IV)
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	Li ion Rechargeable battery pack 18650
Angle of light beam	7° narrow beam to 37° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 5 hrs (level III) 10 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 169.3 mm
Weight in air	245 g (including battery)
Buoyancy in seawater	-121 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass
Lanyard	Included



- 4 Levels of brightness and SOS controlled by a reliable push button design
- Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color
- Twist the front to change the focus (Turning force increases with depth)
- BATCELL 18650 Li ion Rechargeable Battery
- Comes with USB charger
- Comes with random color outdoor dry bag

CF450 M

450 lumens

5X Focusable

Slim Size

Changeable Focus LED Light



Available in 2 colors

SPECIFICATIONS

Light source	Cree LED
Light output	450 Lm
Casing material	Aluminum alloy. Anti-corrosive anodized
Power source	3xAAA alkaline or Ni-MH batteries
Angle of light beam	7° to 37° adjustable
Color temperature	6500K
Burn time	Up to 4hrs
Maximum depth	100 m tested
Size	Dia. 35.5 x L. 121.5 mm
Weight in air	193 g (including batteries)
Buoyancy in seawater	-81 g (including batteries)
Switching system	Magnetic Swivel
Front glass	Tempered optical glass & Convex Lens
Lanyard	Included



1. Twist the front to change the focus (Turning force increases with depth)
2. Magnetic Swivel Switch allows for one hand operation
3. 3xAAA stand-alone battery holder
4. CF 450 M LED with Glove
5. CF 450 M LED with Pouch
6. CF 450 M LED with Pouch and Glove

EASY CLIP Rainbow Color Light



SPECIFICATIONS

- Available fifteen color output –Red, Green, Orange, Blue, Purple, Yellow, Light Blue, Flash red, Flash green, Flash orange, Flash blue, Flash purple, Flash yellow, Flash light blue automatically run all fourteen modes.
- 12-24 hrs of burn time
- 2 x CR2032 batteries
- Dia. 32 x L. 38 mm
- 100 meter tested
- Lanyard included
- 23 g (including batteries) weight in air
- -3 g (including batteries) buoyancy in seawater

EASY CLIP Light with Flash



SPECIFICATIONS

- Available six color output – Blue, Red, Green, Flash Blue, Flash Red, Flash Green
- Up to 36 hrs of burn time
- 2 x CR2032 batteries
- Dia. 32 x L. 38 mm
- 100 meter tested
- Lanyard included
- 23 g (including batteries) weight in air
- -3 g (including batteries) buoyancy in seawater

HL1000_{XWN}

1000 / 500
lumens / lumens
WIDE SPOT



Li ion Rechargeable Battery Extra Wide / Narrow Beam LED Head Light

100° WIDE BEAM
8° NARROW BEAM



SPECIFICATIONS

Light source	5 x Cree LED
Light output (Flood beam)	100 Lm (level I), 250 Lm (level II) 500 Lm (level III), 1000 Lm (level IV)
Light output (Spot beam)	500 Lm
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	Li ion Rechargeable battery pack BATCELL I8650
Angle of light beam	100° wide beam and 8° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 44 mm
Weight in air	219 g (including battery)
Buoyancy in seawater	-86 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



- 4 Levels of brightness for Flood beam mode and 1 level of brightness for Spot beam mode controlled by a reliable push button design.
- BATCELL I8650 Li ion Rechargeable Battery
- Battery level indicator built-in : Blue color / Green color / Red color / Flash Red color
- Angle of light beam

HL1000_N 1000 lumens

Li ion Rechargeable Battery Narrow Beam LED Head Light



FILREDHLN Red filter for HL 1000N. Sold separately.



SPECIFICATIONS

Light source	Cree LED
Light output	100 Lm (level I), 250 Lm (level II) 500 Lm (level III), 1000 Lm (level IV)
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	Li ion Rechargeable battery pack BATCELL I8650
Angle of light beam	8° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 41 mm
Weight in air	205 g (including battery)
Buoyancy in seawater	-74 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



4 levels of brightness and SOS controlled by a reliable push button design



BATCELL I8650 Li ion Rechargeable Battery



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color

HL1000_{xw} 1000 lumens



Li ion Rechargeable Battery Extra Wide Beam LED Head Light



Built-in red color led enhances focusing performance

SPECIFICATIONS

Light source	2 x Cree LED + 2 x XPE Red LED
Light output	100 Lm (level I), 250 Lm (level II) 500 Lm (level III), 1000 Lm (level IV)
Light output (Red color mode)	150 Lm
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	Li ion Rechargeable battery pack BATCELL I8650
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 38.8 mm
Weight in air	207 g (including battery)
Buoyancy in seawater	-76 g (including battery)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass

HL450_N 450 lumens

Narrow Beam LED Head Light



FILREDHLN Red filter for HL 450N. Sold separately.

SPECIFICATIONS

Light source	Cree LED
Light output	45 Lm (level I), 113 Lm (level II) 225 Lm (level III), 450 Lm (level IV)
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	3 x AAA alkaline batteries
Angle of light beam	8° narrow beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 41 mm
Weight in air	187 g (including batteries)
Buoyancy in seawater	-56 g (including batteries)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



4 levels of brightness and SOS controlled by a reliable push button design



3 x AAA alkaline batteries



Battery level indicator built-in: Blue color / Green color / Red color / Flash Red color

HL450_{xw} 450 lumens



Extra Wide Beam LED Head Light



Built-in red color led enhances focusing performance

SPECIFICATIONS

Light source	2 x Cree LED + 2 x XPE Red LED
Light output	45 Lm (level I), 113 Lm (level II) 225 Lm (level III), 450 Lm (level IV)
Light output (Red color mode)	100 Lm
Casing material	Aluminum alloy light head and Polycarbonate body
Power source	3 x AAA alkaline batteries
Angle of light beam	120° wide beam
Color temperature	6500K
Burn time	2 hrs (level IV), 4 hrs (level III) 8 hrs (level II) and 20 hrs (level I)
Maximum depth	100 m tested
Size	Dia. 36.8 x L. 84.4 mm with light head dia. 38.8 mm
Weight in air	189 g (including batteries)
Buoyancy in seawater	-58 g (including batteries)
Switching system	Push button with battery indicator
Front glass	Tempered optical glass



Green Spot light & Red Spot light



SPECIFICATIONS

Light source	: Green Laser
Light output	: Below 1 mW
Casing material	: Aluminum alloy. Anti-corrosive anodized
Power source	: 2 x AAA alkaline or Ni-MH batteries
Wavelength	: 520nm
Burn time	: Up to 12 hrs
Maximum depth	: 100 m tested
Size	: Dia. 19 x L. 168.6 mm
Weight in air	: 89 g (including batteries)
Buoyancy in seawater	: -54 g (including batteries)
Switching system	: Twisting Bezel
Front glass	: Tempered optical glass
Lanyard	: Included

GREEN SPOT LIGHT

RED SPOT LIGHT

Light source	: Red Laser
Light output	: Below 1 mW
Casing material	: Aluminum alloy. Anti-corrosive anodized
Power source	: 2 x AAA alkaline or Ni-MH batteries
Wavelength	: 650nm
Burn time	: Up to 12 hrs
Maximum depth	: 100 m tested
Size	: Dia. 19 x L. 154.1 mm
Weight in air	: 82 g (including batteries)
Buoyancy in seawater	: -51 g (including batteries)
Switching system	: Twisting Bezel
Front glass	: Tempered optical glass
Lanyard	: Included



Operate with 2 x AAA batteries



CLIPMNTSPOT Mounting clip for Green Spot Light and Red Spot Light. Sold separately.

Protective Case Series



Model :	PC101 A	PC102 A	PC103 A	PC104 A	PC105 A	PC106 A
Outer Dimension :	225 x 180 x 100 mm	350 x 270 x 120 mm	340 x 310 x 120 mm	360 x 285 x 190 mm	420 x 360 x 130 mm	420 x 360 x 190 mm
Inner Dimension :	200 x 135 x 85 mm	325 x 210 x 110 mm	310 x 250 x 107 mm	330 x 270 x 175 mm	380 x 310 x 120 mm	380 x 310 x 180 mm

COMBO PACK SERIES

AL 450 NM Tail II Spotter
Narrow Beam Aluminum LED Light with Tail Switch Button

AL 1800NP II
Li ion Rechargeable Battery Narrow Beam LED Light

Easy Clip
Rainbow Color light



AL 250
Multi-Function Aluminum LED Light

AL 1800NP II
Li ion Rechargeable Battery Narrow Beam LED Light

Easy Clip
Rainbow Color light



AL 450 NM Tail II Spotter
Narrow Beam Aluminum LED Light with Tail Switch Button

AL 1300NP
Li ion Rechargeable Battery Narrow Beam LED Light

Easy Clip
Rainbow Color light



AL 450 WM Tail
LED Aluminum Diving Light with Tail Switch Button

AL 1300NP
Li ion Rechargeable Battery Narrow Beam LED Light

Easy Clip
Rainbow Color light



COMBO PACK SERIES

AL 450 NM Tail II Spotter
Narrow Beam Aluminum LED Light with Tail Switch Button

AL 1300WP
Li ion Rechargeable Battery Wide Beam LED Light

Easy Clip
Rainbow Color light



AL 450 WM Tail
LED Aluminum Diving Light with Tail Switch Button

AL 1300WP
Li ion Rechargeable Battery Wide Beam LED Light

Easy Clip
Rainbow Color light



AL 250
Multi-Function Aluminum LED Light

AL 1300NP
Li ion Rechargeable Battery Narrow Beam LED Light

Easy Clip
Rainbow Color light



AL 250
Multi-Function Aluminum LED Light

AL 1300WP
Li ion Rechargeable Battery Wide Beam LED Light

Easy Clip
Rainbow Color light



CAMERA TRAY 34



Camera Tray 34 with 34cm long tray. Two 1" Ball joint arms with no-slip grip. Compatible with Smart Phone Housings e.g. Iphone, Samsung, Huawei

CAMERA TRAY 27



Camera Tray 27 with 27cm long tray. Two 1" Ball joint arms with no-slip grip. Compatible with Olympus TG4/TG5 Housings.

BBGPTray

Go Pro Tray



Go Pro Hot Shoe Adapter



Go Pro Light Adaptor



Go Pro Kit sets

GP4200 Kit

- 1 pc. of Double Clip (CLP02)
- 1 pc. of Go Pro Tray (BBGPTRAY)
- Light not included



GP450 Kit

- 2 pcs. of Mounting Clip (CLIPMINTCF)
- 2 pcs. of Double Clip (CLP02)
- 2 pcs. of Sea & Sea Standard (DA009)
- 1 pc. of Go Pro Tray (BBGPTRAY)
- Lights not included



GP1300 Kit

- 2 pcs. of Double Clip (CLP02)
- 2 pcs. of Sea & Sea Standard (DA009)
- 1 pc. of Go Pro Tray (BBGPTRAY)
- Lights not included



Protective Case for Go Pro Tray Kit Set

- 1 pc. of ALI 300WP
- 1 pc. of ALI 300XWP
- 2 pcs. of Double Clip (CLP02)
- 2 pcs. of Sea & Sea Standard (DA009)
- 1 pc. of Go Pro Tray (BBGPTRAY)



EXTENDAGPTRAY

Extendable Go Pro Tray



Extend from 176mm to 287mm

SINGLEARMTRAY

Single Arm Go Pro Tray



FLEXICAMERATRAY 27

7" Flexi Arm Camera Tray 27



FLEXICAMERATRAY 34

7" Flexi Arm Camera Tray 34



FLEXIGPTRAY

7" Flexi Arm Go Pro Tray



FLEXISINGLEARMTRAY

7" Flexi Arm Single Arm Tray



FLEXIEXTENDGPTRAY


7" Flexi Arm Extendable Go Pro Tray



CURVE SINGLE ARM TRAY



Compatible with Go Pro and Olympus Housings



45 DEGREE BALL JOINT



For Extendable Tripod Plate and Extendable Tripod Camera Tray



EXTENDABLE CAMERA TRAY



Extend from 200mm to 300mm
Compatible with Action Camera and Smart Phone Housings



Extend from 200mm to 300mm

EXTENDABLE TRIPOD PLATE



Extend from 200mm to 300mm
Comes with three pieces of 45 Degree Ball Joint



Easy assemble with double clip and arms.
Double clip and arms sold separately



EXTENDABLE TRIPOD CAMERA TRAY



Extend from 200mm to 300mm
Comes with three pieces of 45 Degree Ball Joint
Compatible with Action Camera and Smart Phone Housings



Extend from 200mm to 300mm

FLUORODIVE Kit sets

Science has discovered corals contain Fluorescent Proteins invisible to the naked eye that jump into view using innovative high-intensity fluorolights and filters.

Bigblue Fluorodive Kits provide everything you need to experience this incredibly beautiful effect. You get specially designed filters to precisely match the coral fluorescence wavelength, and yellow blue-barrier filters to increase the intensity of the colors emitted by the corals. Our innovative design is the only one that allows you to easily switch between blue and white light to accommodate changes in dive conditions.

These kits are suitable for night divers, resorts, science institutions, ecological monitoring groups and specialty photographers.

Truly there is nothing that can match the beauty of witnessing coral fluorescence on your next night dive!



Photos of the fluorescence stimulated by the specific wavelength and captured through a barrier filter


FDKNP33	AL1300NP / AL1300NP Tail Fluorodive Kit
FDK35	CF450M / CF1300P / AL1300WP / AL1300XWP / AL1300WP Tail / AL1800WP / CF1800P / BLACK MOLLY VI / BLACK MOLLY VII Fluorodive Kit
FDK38	CF450 / CF1200P / AL1200WP / AL1200XWP / AL1200WP Tail / BLACK MOLLY II / BLACK MOLLY III Fluorodive Kit
FDK44	VL4600P / VTL2900P Fluorodive Kit
FDK55	VTL4200P / VL11000P / VL9000P Tri Color Fluorodive Kit
FDK63	CB7200P / CB11000P / VTL9000P VTL9000P Max / VTL11000P / VTL13500P Max Fluorodive Kit



Yellow Mask Blue Filter

Camera Filters

Camera filters are available for you to capture the macro or wide angle photos or videos of the memorable aquatic creatures.



FILFLUOR015000

Fluorodive filter for VL 20000P Pro Mini / VL 20000P Pro Mini Tri Color / CB16500P



Batteries & Chargers



BATCELL18650

Battery for AL1300NP / AL1300WP / AL1300XWP / AL1300NP Tail / AL1300WP Tail / CF1300P / HLI1000XWN / HLI1000XW / HLI1000N / RGBWhite II / AL1200NP IR / AL1200WP IR / AL1300 Strobe / AL1300RAFO

BATCELL26650

Battery for Black Molly VI / Black Molly VII / Black Molly VIII / AL1800NP II / AL1800WP / CF1800P

BATCELL32650

Battery for VL4600P / VTL4200P / TL3800P / VTL2900P / TL2900P / VL4600PB / VTL4200PB / VTL2900PB

CR2032

Battery for Easy Clip Light / Controller



BATCELL18650x3

Battery for CB 4000P / VL6200P / CB4000PBRC

BATCELL18650x4

Battery for VLI1000P / VTL9000P / VTL9000P Max / TL5200P / VL9000P Tri Color / VTL1000P / VLI1000PBRC / VTL9000PB

BATCELL21700x4

Battery for CB7200P / CB11000P / CB7200PB / CB11000PBRC / VTL13500P Max / TL8000P Mini

BATCELL18650x7

Battery for VL20000P Pro Mini / VL20000P Pro Mini Tri Color / CB16500P / TL9000P / VL20000PBRC / CB16500PBRC



BATCELLCANISTER

Battery for TL5200P Backmount / Sidemount / VTL9000P Backmount / Sidemount

BATCELL18650x4SUPREME

Battery for TL3800P Supreme

BATCELL21700x4 SUPREME

Battery for TL3800P Supreme Pro

BATCELL21700x8

Battery for VL36000P / CB30000P II / VL36000PBRC



BATCELL60000

Battery for VL65000P / CB60000P

BATCHR60000

Charger for VL65000P / CB60000P

BATCHR21700x8

Charger for VL36000P / CB30000P II / VL36000PBRC

BATCHR18650x7

Charger for VL20000P Pro Mini / VL20000P Pro Mini Tri Color / CB16500P / TL9000P / VL20000PBRC / CB16500PBRC



BATCHR21700x4

Charger for CB7200P / CB11000P / CB7200PB / CB11000PBRC / VTL13500P Max / TL8000P Mini



BATCHR21700x4 SUPREME

Charger for TL3800P Supreme Pro



BATCHR18650x3

Charger for CB4000P / VL6200P / CB4000PBRC



BATCHR18650x4

Charger for VLI1000P / VTL9000P / TL5200P / VL9000P Tri Color / VTL9000P Max / VLI1000PBRC / VTL11000P / VTL9000PB



BATCHR18650x4 SUPREME

Charger for TL3800P Supreme



BATCHRCANISTER

Charger for TL5200P Backmount / Sidemount VTL9000P Backmount / Sidemount



BATCHRUSB

Charger for ALI300NP / ALI300WP / ALI300XWP / ALI300NP Tail / ALI300WP Tail / CF1300P / ALI300RAFO / Black Molly VI / Black Molly VII / Black Molly VII B / HLI1000XW / HLI1000N / HLI1000XWN / RGB White II / ALI200NPIR / ALI200WPIR / ALI300 Strobe / VTL2900P / TL2900P / VTL2900PB / VTL4200PB / VTL4200P / VL4600P / VL4600PB / TL3800P / ALI800NP II / ALI800WP / CF1800P / BATCELL18650 / BATCELL26650 / BATCELL32650

Accessories



AF 55

Ambient filter for VLI1000P / VLI1000PBRC / VL9000P Tri Color For 10-15 meter depth



AF 63

Ambient filter for CB7200P / CB7200PB / CB11000P / CB11000PBRC / VTL9000P / VTL9000PB / VTL9000P Max / VTL11000P / VTL13500P Max For 10-15 meter depth



AF 70

Ambient filter for VL20000P Pro Mini / VL20000P Pro Mini Tri Color / VL20000PBRC / CB16500P / CB16500PBRC For 10-15 meter depth



AF 85

Ambient filter for VL36000P / VL36000PBRC / CB30000P II For 10-15 meter depth



AF 55-LB

Ambient filter for VLI1000P / VLI1000PBRC / VL9000P Tri Color For 5-10 meter depth



AF 63-LB

Ambient filter for CB7200P / CB7200PB / CB11000P / CB11000PBRC / VTL9000P / VTL9000PB / VTL9000P Max / VTL11000P / VTL13500P Max For 5-10 meter depth



AF 70-LB

Ambient filter for VL20000P Pro Mini / VL20000P Pro Mini Tri Color / VL20000PBRC / CB16500P / CB16500PBRC For 5-10 meter depth



AF 85-LB

Ambient filter for VL36000P / VL36000PBRC / CB30000P II For 5-10 meter depth

CONTROLLER

Remote Control for VL36000PBRC / VL20000PBRC / CB16500PBRC / VLI1000PBRC / CB11000PBRC / CB4000PBRC



2M OPTICAL FIBRE

2 Meters Optical fibre for VL36000PBRC / VL20000PBRC / CB16500PBRC / VLI1000PBRC / CB11000PBRC / CB4000PBRC



OPTICAL FIBRE

1 Meter Optical fibre for VL36000PBRC / VL20000PBRC / CB16500PBRC / VLI1000PBRC / CB11000PBRC / CB4000PBRC



TLGGLOVE

Goodman glove for any light with a two-prong mounting square



NPGGLOVEM

Neoprene glove for Mini Light




NPGGLOVE

Neoprene glove for ALI300NP / ALI300WP / ALI300XWP / ALI300NP Tail / ALI300WP Tail / ALI200NP IR / ALI200WP IR



PISTOLGRIPHANDLE

Pistol Grip Handle for any light with a two-prong mounting square



GHA-01C

Goodman handle with connector for any light with a two-prong mounting square



SFGHA-01C

Slim Fit Goodman handle with connector for any light with a two-prong mounting square

Accessories



LANTHANDLE

Lantern style handle



FILFLUORO I 5000

Fluorodive filter for CB16500P / VL20000P Pro Mini / VL20000P Pro Mini Tri Color



FDMASKYL

Yellow filter for Fluorodiving



YELLOW PLATE

Yellow plate for Fluorodiving



SNOOT 35

Snoot Connector for AL1300WP / AL1300XWP / AL1300WP Tail / RGB White II / AL1800WP



SNOOT 38

Snoot Connector for AL1200WP / AL1200XWP / AL1200WP Tail / RGB White



SNOOT 50

Snoot Connector for CB4000P / CB4000PBRC



SNOOT 55

Snoot Connector for VL6000P



SNOOT 63

Snoot Connector for CB7200P / CB11000P / CB7200PB / CB11000PBRC



FILRED35

Red filter for AL1300WP / AL1300XWP / AL1300WP Tail / AL1800WP



FILREDSM

Red filter for AL1200WP / AL1200XWP / AL1200WP Tail



FILRED63

Red filter for VTL11000P / VTL13500P Max



FILREDNP

Red filter for AL1300NP / AL1300NP Tail



FILREDHLN

Red filter for HL1000N / HL450N



FILYELG

Yellow filter for VTL4200P / VLI1000P / VTL4200PB / VLI1000PBRC



FILYEL35

Yellow filter for AL1300WP / AL1300XWP / AL1300WP Tail / Black Molly VII / Black Molly VIIB / AL1800WP



FILYEL44

Yellow filter for VL4600P / VL4600PB / VTL2900P / VTL2900PB / HL1000XWN



FILYEL63

Yellow filter for VTL9000P / VTL9000P Backmount / Sidemount / VTL9000P Max / VTL11000P / VTL13500P Max / VTL9000PB



FILYELSM

Yellow filter for AL1200WP / AL1200XWP / AL1200WP Tail / Black Molly III



CLIPMNTSPOT

Mounting clip for Green Spot Light / Red Spot Light



CLIPMNTAL

Mounting clip for AL1300WP / AL1300XWP / CF1300P / AL1200WP IR



CLIPMNTCF

Mounting clip for CF450M / AL450WM Tail / AL1300WP Tail



GO PRO MOUNT

Go Pro Mount for Go Pro Camera



1" BALL JOINT

1" Ball Joint fit for any light with a two-prong mounting square



SPRING CORD

Length : 330mm



EASY RELEASE MOUNT

Easy Release Mount fit for helmet / DPV



NPHOODMS

Neoprene hood for one light holster



NPHOODMD

Neoprene hood for two light holster



NRPPOUCH

Neoprene pouch with retractor for AL1300NP / AL1300WP / AL1300XWP / AL1300NP Tail / AL1300WP Tail / AL1200NPIR / AL1200VPIR



NRPPOUCHM

Neoprene pouch with retractor for Mini Light



GF63

Globe filter for CB7200P / CB7200PB / CB11000P / CB11000PBRC / VTL13500P Max / VTL9000P / VTL9000PB / VTL9000P Max / VTL11000P For 270° beam angle



GF70

Globe filter for VL20000 Pro Mini / VL20000P Pro Mini Tri Color / VL20000PBRC / CB16500P / CB16500PBRC For 270° beam angle



GF85

Globe filter for VL36000P / VL36000PBRC / CB30000P II For 270° beam angle

Accessories

Outdoor Dry Bags



3L	5L	7L	15L	20L
Dia. 140 x L. 330 mm	Dia. 170 x L. 380 mm	Dia. 180 x L. 510 mm	Dia. 240 x L. 540 mm	Dia. 240 x L. 600 mm
Available in 5 colors Yellow, Green, Pink, Light Blue, Blue	Available in 5 colors Yellow, Green, Pink, Light Blue, Blue	Available in 6 colors Yellow, Green, Pink, Light Blue, Blue, Black	Available in 5 colors Yellow, Green, Blue, Black, Orange	Available in 5 colors Yellow, Green, Blue, Black, Orange

Easy Release Mount Series



Easy Release Glove



Easy Release Goodman Handle




Easy Release GoPro Mount Glove



Easy Release Slim Fit Goodman Handle

Photo/Video Arms & Accessories

Float Arms Series



9" Float Arm

Dia. 70 x 228mm
Weight above water : 281g
Buoyancy lift : 360g



9" Jumbo Float Arm

Dia. 90 x 228mm
Weight above water : 349g
Buoyancy lift : 697g



13" Float Arm

Dia. 70 x 330mm
Weight above water : 430g
Buoyancy lift : 612g

Flexi Arms Series



7" Flexi Arm



9" Flexi Arm



6" Flexi Arm Hot Shoe YS Adapter



6" Flexi Arm Hot Shoe Ball Adapter



YS Adapter

Photo/Video Arms & Accessories

Clips

- Made of T6061 grade aluminum
- Available in 3 versions: long double clip, double clip and a triple clip
- Ergonomic handle makes it easy to twist on and off



Long CLP02 Double clip

Length : 81mm



CLP 02 Double clip

Length : 64mm



CLP 03 Triple clip

Arms

- Full T6061 grade aluminum
- Available in 4 lengths: 5", 8", 12", 16"



5" Arm



8" Arm



12" Arm



16" Arm

For 1" ball joint to connect to extend the connection



DA Series



DA001

Hot Shoe Adapter



DA002

Sea & Sea Adapter



DA003

Light & Motion Adapter



DA004

Standard Dovetail Plate



DA005

8mm Thread



DA006

Sea & Sea Light Adapter



DA007

Sea & Sea Hot Shoe Adapter



DA008

Sea & Sea Medium



DA009

Sea & Sea Standard



DA010

Base Plate Ball Mount



DA011

T-Groove Adapter



DA012

Universal Mount Base



DA013F

1/4" Thread Adapter



DA013M

1/4" Thread Adapter



DA014

Ikelite 200 Strobe Adapter



DA015

Single Ball Arm with Sea & Sea Adapter



DA016

UK Light Adapter



DA017

Standard Dovetail



DA018

Inon Z Series Strobe Adapter



DA022

Slot Stay



DA023

6mm Thread Adapter

Specifications subject to change without prior notice.



highblue®

Lifestyle

OUTDOOR ADVENTURE GEAR



30L Backpack
Camouflage

Size : Dia. 270 x L.670 mm
Available in 5 colors
Camo Blue, Camo Brown.
Camo Green, Camo Grey, Camo Pink



3L Outdoor Dry Bag
Camouflage

Size: Dia. 140 x L.330 mm
Available in 5 colors
Camo Blue, Camo Brown.
Camo Green, Camo Grey, Camo Pink



Sport Water Bottle
Camouflage

Size: Dia. 80 x L.273 mm
Volume: 800mL (27 oz)
Weight : 360g
Available in 2 colors
Camo Blue, Camo Pink

Our Distributors & Dealers



Aruba / Bonaire / Curacao Distributor : Palm Trading Bonaire NV

Contact Person : Joyce Sonneveld
E-mail : sales@palmtradingnv.com
Phone : 599 717 2072
Mail : Hanchi Amboina 5, Kralendijk
Bonaire Dutch Caribbean



Australia Distributor : Adreno

Contact Person : Sam Cox
E-mail : sam@adreno.com.au
Phone : 61-07-3391-2299
Mail : 2A / 605 Zillmere Road,
Aspley, QLD 4034 , Australia



Austria Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 0 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Belgium/ Netherlands / Luxembourg Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 0 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Brazil Distributor : Seasub

Contact Person : Pablo Y. Varela
E-mail : pablo@seasub.com.br
Phone : 55-11-38328342
Mail : Rua Baumann, 1039/1051,
Cep 05318000,
Sao Paulo, Brazil



Canada Distributor : Pacific Scuba Industries

Contact Person : Michael Joseph &
Laura Valente
E-mail : laurabigblue@outlook.com
Phone : 778-834-0184
Mail : Unit A11-33733 King Road
Abbotsford, BC,
V2S 7M9, Canada



Czech Republic Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 (0) 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



France / Europe Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 (0) 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Germany Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 (0) 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Greece / Croatia Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 (0) 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Indonesia Distributor : DiveSea Indonesia

Contact Person : Chatra Hapsoro
E-mail : bigblue.id@gmail.com
Phone : 62-82145490450
Mail : Metro Park Residence, Unit MA-LG-05,
JL. Pilar Mas Utama Raya Kav 28,
Kebon Jeruk, Jakarta Barat 11520 Indonesia



Italy/ Malta Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 (0) 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Japan Distributor : Zero Co., Ltd.

Contact Person : Katsuhiko Saotome
E-mail : zero@zero-zero.co.jp
Phone : 81-3-5721-1906
Fax : 81-3-5721-1910
Mail : 1-11-5 Takaban, Meguro-Ku,
Tokyo, Japan



Korea Distributor : King Sports

Contact Person : Mr. Chang / Yun Hee Chang
E-mail : kingdive@kingsports.co.kr
Phone : 82-2-3628251
Mail : 35-4, 1GA, Manri-Dong, Chung-Gu,
Seoul, Korea



Kuwait Dealer : IImunz Marine Co.

Contact Person : Abdulrahman Al-Serheed
E-mail : IImunz@ilmunz.com
Phone : +965 95500969
Mail : Creative Design Center , Block 1 , Street 10,
Building 63, Store 2.2,
Shuwaikh Industrial 1, Kuwait



Malaysia Distributor : Prestige Scuba Sdn. Bhd.

Contact Person : Carol
E-mail : info@prestigesuba.com
Phone : 60-374-956777
Mail : 14 Jalan SS2/75, SS2,
47300 Petaling Jaya,
Selangor Darul Ehsan, Malaysia



Maldives Dealer : Sea Gear

Contact Person : Hussen Abdulla
E-mail : sales@seagear.com.mv
Phone : +960 3302737
Mail : M. Araliya – Ground Floor – Alhivilaa Magu,
20292 Male, Maldives



Mexico Distributor : Comercializadora UNIF Sa De CV

Contact Person : Tristan Termat
E-mail : tristan@unifmexico.com.mx
Phone : + 52 984 80 311 68
Mail : Calle 4 nte Mza 42 Lote 4-1 Local B Entre
25 y 30 Avenida Col. Centro Localidad :
Playa del Carmen, Q. Roo Municipio :
Solidaridad CP: 77710 Mexico



New Zealand Distributor : Sea Tech Ltd.

Contact Person : Dave Moran
E-mail : info@seatech.co.nz
Phone : 64-9-5210684
Mail : 47 Tautari St. Orakei. Auckland 1071,
New Zealand



Philippines Distributor : Dive Supply Subic, INC.

Contact Person : Katherine Tobeo
E-mail : katherine@ceiiph.com
Phone : +63-2-8-708-9995 loc 116
Mail : 2F Babs Building 9304,
Kamagong Cor. Dungon St.,
San Antonio Makati City 1203
Philippines



Poland Distributor : Waterfall

Contact Person : Darek
E-mail : darek@waterfall.pl
Phone : 48-22-484-20-72
Mail : UL. Mirkowska 45,
05-520 Konstancin, Jeziorna,
Poland



Scandinavian Distributor : AquaFun AB

Contact Person : Sales Office
E-mail : info@aquafun.se
Phone : 46-0-40-295-300
Mail : Sangleksgatan 4E, 215 79, Malmo,
Sweden



Singapore Distributor : DiveSea Pte Ltd

Contact Person : Fairuz Ahmad
E-mail : team@divesea.com.sg
Phone : 65-85115164
Mail : 90 Lor 23 Geylang
Agrow Building # 01-03
Singapore 388393



South Africa Distributor: Manex & Power Marine

Contact Person : Gavin Jones
E-mail : gavin.jones@manex.co.za
Phone : 27-021-511-7292
Mail : 9 Paarden Eiland Road, Paarden Eiland,
South Africa



Spain/ Portugal Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 (0) 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Switzerland Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : +33 0 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Russia Distributor : Custom Diving Systems

Contact Person : Yannig Charles
E-mail : contact@cds-pro.com
Phone : + 33 (0) 6 114 81 114
Mail : 563, Rue De La Prairie 73350
Bozel , France



Taiwan Dealer : Indigo Blue Technology Co. Ltd.

Contact Person : Rachel Cheng
E-mail : rachel.cheng@weistech.com.tw
Phone : +886 2 82271619
Mail : 4F-6, No. 258 Lian Cheng Road,
Chung Ho Dist.,
New Taipei City 23553,
Taiwan, ROC



Turkey Distributor : K Pro Doga Sporlari Malzemeleri Tic. Ltd. STI

Contact Person : Akin Kaftanoglu
E-mail : akinkaftanoglu@yahoo.com
Phone : 90-3124334479
Mail : Bulbulderesi Cad. No.: 23/A, Seyranbaglari,
Ankara, Turkey



U.A.E. Distributor : Senyar Marine Equipment

Contact Person : Abdulla Ai Kindi
E-mail : senyar7@gmail.com
Phone : 971-2-666-9999
Mail : P.O. Box 112790, Abu Dhabi, U.A.E.



United Kingdom / Ireland Distributor : Liquid Sports Ltd.

Contact Person : Alastair Ansell
E-mail : alastair@liquidsports.co.uk
Phone : 44-0-7585-935522
Mail : 11 Stag Lane, Berkhamsted,
Hertfordshire, HP4 1FJ, UK

bigblue®

THE BRIGHTER IDEA

Visit Us
on website



Like Us
on facebook



www.bigbluelights.com
www.bigblue.com.hk

Headquarters :

Bossk International Company Limited

Contact Person : Oscar Tong

E-mail : oscar@bigblue.com.hk

Phone : 852-3568-0773

Fax: 852-3998-3127

Mail : Room 818,8/F, Po Yip Building, 23.

Hing Yip Street, Kwun Tong, Hong Kong

US Sales Office : BosskUSA / Bigblue Dive Lights

Contact Person : Tim Ratcliffe

E-mail : sales@bigbluedivelights.com

Phone : 727-442-2300

Fax: 727-499-7117

Mail : 1710N Hercules Ave, Suite 103, Clearwater,
FL 33765 USA